




BA16
PC LED Bar
Surface Mounted



HOUSING
Polycarbonate extruded monoblock housing
IP40 Protection
Electrical Safety Class III

Body Color Options

9016
White


OPTIC
PC Diffuser
IEC/EN 62471 Photo-Biologic Protection RG0
UGR (CIE Pub.117):21

Optic Options

120°

LED
SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index
80⁺
Ra>80

CCT

2700K 3000K 4000K 5000K 5700K 6500K Blue Green Red Amber

CONTROL
Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
198~264VAC
50~60Hz
PF>0.95
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features
24V DC
INPUT

STANDARDS
Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1
-


BA16

PC LED Bar

Surface Mounted



BA15-AD10
120 LED/m




Power	Lum. Flux	Efficiency
5W	464 lm	91 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



BA15-BD10
168 LED/m



Power	Lum. Flux	Efficiency
5W	430 lm	85 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

BA16 - BD10 - 014 - 8		65	S	-9016 - 0120 -	2	X	X	S	20			
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
BA16	BD10 CD10	014: 14W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K MB: Amber RD: Red GR: Green BL: Blue	S: Standart	9016: Beyaz	0120: 120°	2: 24V			S: Standart K: İki Uç Kablolu W: IP65 Soketli	20: IP20