



BA22
LED Bar
Surface Mounted



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP40 Protection
Electrical Safety Class III

Body Color Options



9006
Gray

OPTIC

UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



120°

LED


SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



Ra>80

CCT



2700K

3000K

4000K

5000K

5700K

6500K

Blue

Green

Red

Amber

CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
198~264VAC
50~60Hz
PF>0.95
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



INPUT



INPUT

STANDARDS




Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1
-

BA22

LED Bar

Surface Mounted

 BA22-AU10 60 LED/m		Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	- lm	- lm/W	Width	- cm
 BA22-BU10 120 LED/m		Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	- lm	- lm/W	Width	- cm
 BA22-CU10 168 LED/m		Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	- lm	- lm/W	Width	- cm

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

BA22- BD10- 014 - 8 65 S -IPPU -0120- 2 X X S 65												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
BA22	AU10 BU10 CU10	014: 14W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K MB: Amber RD: Red GR: Green BL: Blue	S: Standart H: Yüksek	IPPU: Poliüretan	0120: 120°	1: 12V 2: 24V			S: Standart K: İki Uç Kablolulu W: IP65 Soketli	65: IP65