



BA23
LED Bar
Surface Mounted



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP40 Protection
Electrical Safety Class III

Body Color Options



OPTIC

PC Diffuser
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT



CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
198~264VAC
50~60Hz
PF>0.95
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features






STANDARDS

Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1
-

BA23
LED Bar
Surface Mounted

 BA23-AD10 60 LED/m		Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	783 lm	55 lm/W	Width	- cm
 BA23-BD10 120 LED/m		Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	971 lm	67 lm/W	Width	- cm
 BA23-CD10 168 LED/m		Power	Lum. Flux	Efficiency	Packaging Sizes	
		14W	1126 lm	77 lm/W	Width	- cm

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

BA23- BD10- 014 - 8		65	S	-9006-0120-	2	2	X	S	40			
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
BA23	AD10 BD10 CD10	014: 14W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K MB: Amber RD: Red GR: Green BL: Blue	S: Standart	9006: Gray	PCD8: PC %80	2: 24V	2: 24V		S: Standart K: İki Uç Kablololu W: IP65 Soketli	40: IP40