




BS12-BS24
LED
Strip



HOUSING

OPTIC

LED		Color Rendering Index	80 ⁺							
			Ra>80							
			CCT							
2700K	3000K	4000K		5000K	5700K	6500K	Blue	Green	Red	Amber
CONTROL		Additional Features	12V DC		24V DC					
			INPUT		INPUT					
			-							
			-							
			-							
			-							

STANDARDS

Luminaire Standarts	-
Driver Standarts	-

BS12-BS24
LED
Strip

►10mm

 BS24-0060 60 LED/m	Power	Lum. Flux	Efficiency	Packaging Sizes	
	14W	1267 lm	90 lm/W	Width	- cm
				Length	- cm
				Heigth	- cm
				Amount per ctn.	- pcs.
				Ctn. weighth	- kg
 BS24-0120 120 LED/m	Power	Lum. Flux	Efficiency	Packaging Sizes	
	14W	1379 lm	97 lm/W	Width	- cm
				Length	- cm
				Heigth	- cm
				Amount per ctn.	- pcs.
				Ctn. weighth	- kg
 BS24-0168 168 LED/m	Power	Lum. Flux	Efficiency	Packaging Sizes	
	14W	1636 lm	113 lm/W	Width	- cm
				Length	- cm
				Heigth	- cm
				Amount per ctn.	- pcs.
				Ctn. weighth	- kg
 BS12-0060 60 LED/m	Power	Lum. Flux	Efficiency	Packaging Sizes	
	14W	1144 lm	81 lm/W	Width	- cm
				Length	- cm
				Heigth	- cm
				Amount per ctn.	- pcs.
				Ctn. weighth	- kg

►5mm

 BS24-5120 120LED/m	Power	Lum. Flux	Efficiency	Packaging Sizes	
	14W	549 lm	110 lm/W	Width	- cm
				Length	- cm
				Heigth	- cm
				Amount per ctn.	- pcs.
				Ctn. weighth	- kg
 BS24-5168 168 LED/m	Power	Lum. Flux	Efficiency	Packaging Sizes	
	14W	521 lm	104 lm/W	Width	- cm
				Length	- cm
				Heigth	- cm
				Amount per ctn.	- pcs.
				Ctn. weighth	- kg

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

BS24 - 0168 - 014 - 8 65 S -XXXX-XXXX- 2 S S S 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
BS12	0060	014: 14W	8: 80	27: 2700K	S: Standart			1: 12V	S: LAMPTIME	S: Standart	S: Standart	20: IP20
BS24	0120			30: 3000K				2: 24V				
	0168			40: 4000K								
	0060			65: 6500K								
	5120			MB: Amber								
	5168			RD: Red								
				GR: Green								
		BL: Blue										