




DB10

Backlight Downlight LED Lighting


Round Recessed



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP54/IP20 Protection
Electrical Safety Class II

Body Color Options



OPTIC

PMMA diffuser with high transmissivity
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT




CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264VAC
50~60Hz
PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protection (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



STANDARDS

Luminaire Standards
Driver Standards
EN 60598-1 - EN 60598-2-2
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

Round Recessed

**The specified luminous flux values may vary by %10.

DB10- 0190 - 020 - 8 40 S - 9016-0120- O S S S E0												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
DB10	0117 0138 0190 0240	006: 6W 012: 12W 015: 15W 020: 20W 025: 25W 030: 30W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: Beyaz 9006: Gri 9005: Siyah	0120: 120°	O: ON-OFF D: DALI	S: LAMPTIME E: Diğer	S: Standart 3: 3 Hours Kit	S: Standart	E0: IP54/20 65: IP65