




DC15

COB Downlight LED Lighting

Square Recessed



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP20 Protection
Electrical Safety Class II


Body Color Options



OPTIC

Aluminium Reflector
UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

COB LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



Ra>80

CCT




CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264 VAC
50~60Hz
PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
-20°C ~ +50°C

Additional Features



STANDARDS

Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-2
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)


DC15

COB Downlight LED Lighting

Square Recessed



DC15-1115




Power	Lum. Flux	Efficiency
8W	1133 lm	94 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



DC15-2115



Power	Lum. Flux	Efficiency
2x8W	1133 lm	94 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DC15-	2115	-	008	-	8	40	S	-	9005	-	0030	-	O	S	S	S	20
GROUP CODE	BODY CODE	POWER	CRI		CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL		DRIVER	KIT	ACSESSORY				IP
DC15	1115 2115	008: 8W	8: 80		27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 9006: Gray 9005: Black	0015: 15° 0030: 30° 0045: 45°	O: ON-OFF D: DALI		S: LAMPTIME E: Other	S: Standart 3: 3 Hours Kit	S: Standart				20: IP20