




DC22

IP65 COB Downlight LED Lighting

Round Surface Mounted



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP65 Protection
Electrical Safety Class I

Body Color Options



OPTIC

UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



Reflector Colors



LED

COB LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT



CONTROL

Rated Input Voltage	220~240VAC
Range of Input Voltage	90~265VAC
Frequency	50~60Hz
Power Factor	PF>0.95
Operating Temperature	-20°C ~ +50°C
Constant Current LED Driver	Over Current Protection (OCP), Over Voltage Protectio (OVP), Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features






STANDARDS

Luminaire Standarts	EN 60598-1 - EN 60598-2-1
Driver Standarts	LVD (EN 61347-1, EN 61347-2-13)
	EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

DC22

IP65 COB Downlight LED Lighting

Round Surface Mounted

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>12W</td><td>864 lm</td><td>87 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	12W	864 lm	87 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
12W	864 lm	87 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>18W</td><td>1982 lm</td><td>98 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	18W	1982 lm	98 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
18W	1982 lm	98 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>32W</td><td>2693 lm</td><td>85 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	32W	2693 lm	85 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
32W	2693 lm	85 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DC22- 0150 - 018 - 8 40 S - 9016- 0045- O S S S 65												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
DC22	0082 0115 0187	012: 12W 018: 18W 032: 32W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 9006: Gray 9005: Black	0045: 45° WH: White BL: Black SR: Rose Gold CR: Chrome SG: Gold MG: Gold Mat SM: Smoked	O: ON-OFF	S: LAMP TIME E: Other	S: Standart	S: Standart	65: IP65