



DC24

COB Downlight LED Lighting

Round Surface Mounted



SURFACE



CE



VOLTAGE



PROTECT.



CLASS I



Ta



MADE IN
TÜRKIYE

HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP20 Protection
Electrical Safety Class I

Body Color Options



9016
White



9006
Gray



9005
Black



All
Colors

OPTIC

Aluminium Reflector
UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



15°



30°



45°

LED

COB LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



Ra>80

CCT



2700K



3000K



4000K



5000K



5700K



6500K

CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264 VAC
50~60Hz
PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



ON/OFF



DIM



STANDARDS

Luminaire Standarts
Driver Standarts
EN 60598-1 - EN 60598-2-1
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

DC24

COB Downlight LED Lighting

Round Surface Mounted

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>20W</td><td>1930 lm</td><td>95 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	20W	1930 lm	95 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
20W	1930 lm	95 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						
		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>30W</td><td>2700 lm</td><td>90 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	30W	2700 lm	90 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
30W	2700 lm	90 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						
		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>40W</td><td>- lm</td><td>- lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	40W	- lm	- lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
40W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DC24- 0254 - 040 - 8 40 S - 9016-0030- O S S S 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
DC24	0163	020: 20W	8: 80	27: 2700K	S: Standart	9016: White	0015: 15°	O: ON-OFF D: DALI	S: LAMPTIME E: Other	S: Standart	S: Standart	20: IP20
	0200	030: 30W		30: 3000K		9006: Gray	0030: 30°					
	0254	040: 40W		40: 4000K		9005: Black	0045: 45°					
						65: 6500K						