




**DC26**  
**COB Downlight LED Lighting**  
Surface Mounted GU10



**HOUSING**  
Electrostatic powder paint coated die cast aluminum housing  
IP20 Protection

**Body Color Options**



**OPTIC**  
-

**LED**  
-


**CONTROL**  
Rated Input Voltage -  
Range of Input Voltage -  
Frequency -  
Power Factor -  
Operating Temperature -  
Constant Current LED Driver -  
-


**STANDARDS**  
Luminaire Standarts -  
Driver Standarts -

DC26

COB Downlight LED Lighting

Surface Mounted GU10

|                                                                                                       |                                                                                   |       |           |            |                 |        |
|-------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------|-----------|------------|-----------------|--------|
| <br><b>DC26-0055</b> |  | Power | Lum. Flux | Efficiency | Packaging Sizes |        |
|                                                                                                       |                                                                                   | GU10  | - lm      | - lm/W     | Width           | - cm   |
|                                                                                                       |                                                                                   |       |           |            | Length          | - cm   |
|                                                                                                       |                                                                                   |       |           |            | Height          | - cm   |
|                                                                                                       |                                                                                   |       |           |            | Amount per ctn. | - pcs. |
|                                                                                                       |                                                                                   |       |           |            | Ctn. weight     | - kg   |
|                                                                                                       |                                                                                   |       |           |            | Deci            | -      |

|                                                                                                       |                                                                                   |       |           |            |                 |        |
|-------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------|-----------|------------|-----------------|--------|
| <br><b>DC26-0060</b> |  | Power | Lum. Flux | Efficiency | Packaging Sizes |        |
|                                                                                                       |                                                                                   | GU10  | - lm      | - lm/W     | Width           | - cm   |
|                                                                                                       |                                                                                   |       |           |            | Length          | - cm   |
|                                                                                                       |                                                                                   |       |           |            | Height          | - cm   |
|                                                                                                       |                                                                                   |       |           |            | Amount per ctn. | - pcs. |
|                                                                                                       |                                                                                   |       |           |            | Ctn. weight     | - kg   |
|                                                                                                       |                                                                                   |       |           |            | Deci            | -      |

\*\*The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

|            |              |           |     |     |            |                                          |       |         |        |     |           |          |    |
|------------|--------------|-----------|-----|-----|------------|------------------------------------------|-------|---------|--------|-----|-----------|----------|----|
| DC26-      | 0060-        | G10       | -   | X   | XX         | X                                        | -     | 9016-   | XXXX-  | X   | X         | X        | 20 |
| GROUP CODE | BODY CODE    | POWER     | CRI | CCT | EFFICIENCY | BODY COLOR                               | OPTIC | CONTROL | DRIVER | KIT | ACSESSORY | IP       |    |
| DC26       | 0055<br>0060 | G10: GU10 |     |     |            | 9016: White<br>9006: Gray<br>9005: Black |       |         |        |     |           | 20: IP20 |    |