




DC27
COB Downlight LED Lighting
Surface Mounted GU10



HOUSING
Electrostatic powder paint coated die cast aluminum housing
IP20 Protection

Body Color Options



OPTIC
-

LED
-


CONTROL
Rated Input Voltage -
Range of Input Voltage -
Frequency -
Power Factor -
Operating Temperature -
Constant Current LED Driver -


STANDARDS
Luminaire Standarts -
Driver Standarts -

DC27

COB Downlight LED Lighting

Surface Mounted GU10

 DC27-0060		Power	Lum. Flux	Efficiency	Packaging Sizes	
		GU10	- lm	- lm/W	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-

 DC27-0070		Power	Lum. Flux	Efficiency	Packaging Sizes	
		GU10	- lm	- lm/W	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DC27-	0060-	G10	-	X	XX	X	-	9016-	XXXX-	X	X	X	20
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP	
DC27	0060 0070	G10: GU10				9016: White 9006: Gray 9005: Black						20: IP20	