



DC28
COB Downlight LED Lighting
Surface Mounted GU10



HOUSING
Electrostatic powder paint coated die cast aluminum housing
IP20 Protection

Body Color Options

9016 White

9006 Gray

9005 Black

All Colors

OPTIC
-

LED
-

CONTROL

Rated Input Voltage	-
Range of Input Voltage	-
Frequency	-
Power Factor	-
Operating Temperature	-
Constant Current LED Driver	-

STANDARDS

Luminaire Standarts	-
Driver Standarts	-

DC28

COB Downlight LED Lighting

Surface Mounted GU10

 DC28-100S		Power	Lum. Flux	Efficiency	Packaging Sizes	
		GU10	- lm	- lm/W	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-

 DC28-100R		Power	Lum. Flux	Efficiency	Packaging Sizes	
		GU10	- lm	- lm/W	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DC28- 100S- G10 - X XX X - 9016-XXXX- X X X X 20													
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP	
DC28	100S 100R	G10: GU10				9016: White 9006: Gray 9005: Black						20: IP20	