


DC29


Downlight LED Lighting

With Lens Recessed




HOUSING
Electrostatic powder paint coated die cast aluminum housing
IP20 Protection

Body Color Options



OPTIC
UGR (CIE Pub.117):9
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



Reflector Colors



LED
SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index




CCT



CONTROL
Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264 VAC
50~60Hz
PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features




STANDARDS

Luminaire Standarts
Driver Standarts
EN 60598-1 - EN 60598-2-2
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

DC29

Downlight LED Lighting

With Lens Recessedt

 DC29-0005	 143x37mm		Power	Lum. Flux	Efficiency	Packaging Sizes	
			5W	576 lm	101 lm/W	Width	- cm
			10W	1154 lm	113 lm/W	Length	- cm
 DC29-0010	 276x37mm		10W	1125 lm	107 lm/W	Height	- cm
			20W	2316 lm	118 lm/W	Amount per ctn.	- pcs.
						Ctn. weighth	- kg
 DC29-0015	 409x37mm		15W	1862 lm	106 lm/W	Deci	-
			30W	3605 lm	119 lm/W		

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DC29- 0010 - 020 - 8 40 S - 9016- 0030- 0 S S S 20													
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP	
DC29	0005	005: 5W	8: 80	27: 2700K	S: Standart	9016: White	0030: 30°	0: ON-OFF D: DALI	S: LAMPTIME E: Other	S: Standart 3: 3 Hours Kit	S: Standart	20: IP20	
	0010	010: 10W		30: 3000K		9006: Gray	0045: 45°						
	0015	015: 15W		40: 4000K		9005: Black	WH: White						SG: Gold MG: Gold Mat SM: Smoked
		020: 20W		65: 6500K			BL: Black						
		030: 30W		SR: Rose Gold									