




DC30

COB Downlight LED Lighting


Round Recessed



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP20 Protection
Electrical Safety Class II

Body Color Options



OPTIC

UGR (CIE Pub.117):9
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



Reflector Colors



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering index (CRI>80)

Color Rendering Index



CCT




CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264 VAC
50~60Hz
PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



STANDARDS


Luminaire Standarts
Driver Standarts


EN 60598-1 - EN 60598-2-2
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

DC30

COB Downlight LED Lighting

Round Recessed

 DC30-0030		Power	Lum. Flux	Efficiency	Packaging Sizes	
		2W	243 lm	82 lm/W	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-

 DC30-0040		Power	Lum. Flux	Efficiency	Packaging Sizes	
		3W	286 lm	89 lm/W	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DC30- 0040- 003 - 8 40 S - 9016- 0030- 0 S S S 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
DC30	0030 0040	002: 2W 003: 3W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 9006: Gray 9005: Black	0030: 30° BL: Black	0: ON-OFF D: DALI	S: LAMPTIME E: Other	S: Standart 3: 3 Hours Kit	S: Standart	20: IP20