




DC40

COB Downlight LED Lighting

Round Surface Mounted ø110



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP20 Protection
Electrical Safety Class I


Body Color Options



OPTIC

UGR (CIE Pub.117):9
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



Reflector Colors



LED

COB LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT



CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264 VAC
50~60Hz
PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



STANDARDS






Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

DC40

COB Downlight LED Lighting

Round Surface Mounted ø110

		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Surface</td><td>24W</td><td>2480 lm</td><td>107 lm/W</td></tr><tr><td>Suspended</td><td>24W</td><td>2480 lm</td><td>107 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Surface	24W	2480 lm	107 lm/W	Suspended	24W	2480 lm	107 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-
Mounting	Power	Lum. Flux	Efficiency																										
Surface	24W	2480 lm	107 lm/W																										
Suspended	24W	2480 lm	107 lm/W																										
Packaging Sizes																													
Width	- cm																												
Length	- cm																												
Heigth	- cm																												
Amount per ctn.	- pcs.																												
Ctn. weighth	- kg																												
Deci	-																												
		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Suspended</td><td>24W</td><td>2480 lm</td><td>107 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Suspended	24W	2480 lm	107 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-				
Mounting	Power	Lum. Flux	Efficiency																										
Suspended	24W	2480 lm	107 lm/W																										
Packaging Sizes																													
Width	- cm																												
Length	- cm																												
Heigth	- cm																												
Amount per ctn.	- pcs.																												
Ctn. weighth	- kg																												
Deci	-																												
		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Suspended</td><td>24W</td><td>2480 lm</td><td>107 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Suspended	24W	2480 lm	107 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-				
Mounting	Power	Lum. Flux	Efficiency																										
Suspended	24W	2480 lm	107 lm/W																										
Packaging Sizes																													
Width	- cm																												
Length	- cm																												
Heigth	- cm																												
Amount per ctn.	- pcs.																												
Ctn. weighth	- kg																												
Deci	-																												
		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Suspended</td><td>24W</td><td>2280 lm</td><td>107 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Suspended	24W	2280 lm	107 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-				
Mounting	Power	Lum. Flux	Efficiency																										
Suspended	24W	2280 lm	107 lm/W																										
Packaging Sizes																													
Width	- cm																												
Length	- cm																												
Heigth	- cm																												
Amount per ctn.	- pcs.																												
Ctn. weighth	- kg																												
Deci	-																												
		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Suspended</td><td>24W</td><td>2480 lm</td><td>107 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Suspended	24W	2480 lm	107 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-				
Mounting	Power	Lum. Flux	Efficiency																										
Suspended	24W	2480 lm	107 lm/W																										
Packaging Sizes																													
Width	- cm																												
Length	- cm																												
Heigth	- cm																												
Amount per ctn.	- pcs.																												
Ctn. weighth	- kg																												
Deci	-																												

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DC40- 1170 - 024 - 8 40 S - 9016- 0045- 0 S S S 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
DC40	1112 1115 1130 1150 1170	024: 24W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 9006: Gray 9005: Black	0030: 30° 0045: 45° WH: White BL: Black SR: Rose Gold CR: Chrome SG: Gold MG: Gold Mat SM: Smoked	0: ON-OFF	S: LAMPTIME E: Other	S: Standart	S: Standart P: Sarkit	20: IP20