




DC43

COB Downlight LED Lighting

Square Surface Mounted 110x110mm



HOUSING
Electrostatic powder paint coated extruded aluminum housing
IP20 Protection
Electrical Safety Class

Body Color Options


9016 White


9006 Gray


9005 Black


All Colors

OPTIC
UGR (CIE Pub.117):9
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options


30°


45°

Reflector Colors


WH WHITE


BL BLACK


SR ROSE GOLD


CR CHROME


SG GOLD


MG GOLD MAT


SM SMOKED

LED
COB LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index


80⁺
Ra>80

CCT


2700K


3000K


4000K


5000K


5700K


6500K

CONTROL
Rated Input Voltage 220~240VAC
Range of Input Voltage 176~264 VAC
Frequency 50~60Hz
Power Factor PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver Over Current Protection (OCP), Over Voltage Protectio (OVP), Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features







ON/OFF

STANDARDS
Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

DC43

COB Downlight LED Lighting

Square Surface Mounted 110x110mm

		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Surface</td><td>24W</td><td>2520 lm</td><td>105 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Surface	24W	2520 lm	105 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Mounting	Power	Lum. Flux	Efficiency																						
Surface	24W	2520 lm	105 lm/W																						
Packaging Sizes																									
Width	- cm																								
Length	- cm																								
Height	- cm																								
Amount per ctn.	- pcs.																								
Ctn. weight	- kg																								
Deci	-																								
		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Suspended</td><td>24W</td><td>2520 lm</td><td>105 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Suspended	24W	2520 lm	105 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Mounting	Power	Lum. Flux	Efficiency																						
Suspended	24W	2520 lm	105 lm/W																						
Packaging Sizes																									
Width	- cm																								
Length	- cm																								
Height	- cm																								
Amount per ctn.	- pcs.																								
Ctn. weight	- kg																								
Deci	-																								
		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Suspended</td><td>24W</td><td>2520 lm</td><td>105 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Suspended	24W	2520 lm	105 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Mounting	Power	Lum. Flux	Efficiency																						
Suspended	24W	2520 lm	105 lm/W																						
Packaging Sizes																									
Width	- cm																								
Length	- cm																								
Height	- cm																								
Amount per ctn.	- pcs.																								
Ctn. weight	- kg																								
Deci	-																								
		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Suspended</td><td>24W</td><td>2520 lm</td><td>105 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Suspended	24W	2520 lm	105 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Mounting	Power	Lum. Flux	Efficiency																						
Suspended	24W	2520 lm	105 lm/W																						
Packaging Sizes																									
Width	- cm																								
Length	- cm																								
Height	- cm																								
Amount per ctn.	- pcs.																								
Ctn. weight	- kg																								
Deci	-																								
		<table><tr><th>Mounting</th><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>Suspended</td><td>24W</td><td>2520 lm</td><td>105 lm/W</td></tr></table>	Mounting	Power	Lum. Flux	Efficiency	Suspended	24W	2520 lm	105 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Mounting	Power	Lum. Flux	Efficiency																						
Suspended	24W	2520 lm	105 lm/W																						
Packaging Sizes																									
Width	- cm																								
Length	- cm																								
Height	- cm																								
Amount per ctn.	- pcs.																								
Ctn. weight	- kg																								
Deci	-																								

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DC43- 1150 - 024 - 8		40	S	- 9005- 0045- O		S	S	S	20			
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
DC43	1112 1115 1130 1150 1170	024: 24W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 9006: Gray 9005: Black	0030: 30° 0045: 45° WH: White BL: Black SR: Rose Gold CR: Chrome SG: Gold MG: Gold Mat SM: Smoked	O: ON-OFF	S: LAMPTIME E: Other	S: Standart	S: Standart P: Sarkit	20: IP20