




D055
IP65 Wall LED Lighting
E27



HOUSING
Electrostatic powder paint coated die cast aluminum housing
IP65 Protection
Electrical Safety Class I

Body Color Options

9016
White

9006
Gray

9005
Black

All
Colors

OPTIC
UGR (CIE Pub.117):19
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options

40°-15°

LED
SMD LED with a minimum lifetime of 100.000 hours
High color rendering index (CRI>80)

Color Rendering Index

80⁺
Ra>80

CCT

2700K

3000K

4000K

5000K

5700K

6500K

CONTROL		Additional Features
Rated Input Voltage	220~240VAC	
Range of Input Voltage	176~264 VAC	
Frequency	50~60Hz	
Power Factor	PF>0.60 (P≤25W) / PF>0.95 (P≥25W)	
Operating Temperature	-20°C ~ +50°C	
Constant Current LED Driver	Over Current Protection (OCP), Over Voltage Protectio (OVP), Short Circuit Protection (SCP), Over Temperature Protection (OTP)	

STANDARDS	
Luminaire Standarts	EN 60598-1 - EN 60598-2-1
Driver Standarts	LVD (EN 61347-1, EN 61347-2-13) EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

D055

IP65 Wall LED Lighting

E27



D055-1110



Power	Lum. Flux	Efficiency
6W	90 lm	15 lm/W

Packaging Sizes	
Width	XX cm
Length	XX cm
Height	XX cm
Amount per ctn.	X pcs.
Ctn. weight	XX kg
Deci	X,XX

ORDER CODE EXPENSION

D055-	1110	-	006	-	8		40		S	-	9016	-	XXXX	-	X		X		X		S		65
GROUP CODE	BODY CODE		POWER		CRI		CCT		EFFICIENCY		BODY COLOR		OPTIC		CONTROL		DRIVER		KIT		ACCESSORY		IP
D055	1110		006: 6W		8: 80		27: 2700K 30: 3000K 40: 4000K 65: 6500K		S: Standart		9016: White 9006: Gray 9005: Black				0: ON-OFF		S: LAMPTIME		S: Standart		S: Standart		65: IP65