



DS10

Slim Downlight LED Lighting


Round Recessed



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP20 Protection
Electrical Safety Class II

Body Color Options



OPTIC

PS diffuser with high transmissivity
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering index (CRI>80)

Color Rendering Index



CCT




CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264VAC
50~60Hz
PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



İLGİLİ STANDARTLAR

Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-2
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

Round Recessed

**The specified luminous flux values may vary by %10.

DS10- 0175 - 024 - 8 40 S -9005-PS76- 0 S S S 20

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
DS10	0085	003: 3W	8: 80	27: 2700K	S: Standart	9016: White	PS76	0: ON-OFF	S: LAMPTIME	S: Standart 3: 3 Hours Kit	S: Standart	20: IP20
	0120	006: 6W		30: 3000K		9006: Gray		D: DALI	E: Other			
	0145	012: 12W		40: 4000K		9005: Black						
	0175	016: 16W		65: 6500K								
	0200	018: 18W										
	0225	020: 20W										
	0300	024: 24W										