



ED10

Emergency LED Lighting

Ceiling



HOUSING

ABS Housing
IP20 Protection
Electrical Safety Class II

Body Color Options



BATTERY

UGR (CIE Pub.117):-
IEC/EN 62471 Photo-Biologic Protection RG0

LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)
Visibility Range 30m

Color Rendering Index



Ra>80

CCT



6500K

CONTROL

Rated Input Voltage 220~240VAC
Range of Input Voltage 176~264VAC
Frequency 50~60Hz
Power Factor -
Operating Temperature -20°C ~ +50°C

Constant Current LED Driver

Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



ON/OFF



Emergency Lighting


STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-22
Driver Standarts -


ED10

Emergency LED Lighting

Ceiling

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>2W</td><td>14 lm</td><td>5 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	2W	14 lm	5 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
2W	14 lm	5 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
ED10-S000																							

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>2W</td><td>14 lm</td><td>5 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	2W	14 lm	5 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
2W	14 lm	5 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
ED10-P000																							

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>2W</td><td>14 lm</td><td>5 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	2W	14 lm	5 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Height</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weight</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
2W	14 lm	5 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Height	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weight	- kg																						
Deci	-																						
ED10-R000																							

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

ED10- S000- 002 - X 65 S - 9016-XXXX- O S S S 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
ED10	S000 P000 R000	002: 2W		65: 6500K	S: Standart	9016: White		O: ON-OFF	S: LAMPTIME	S: Standart 1: 1 Hours Kit	S: Standart	20: IP20