




ED20

Emergency LED Lighting

Wall



HOUSING

ABS Housing
IP20 Protection
Electrical Safety Class II

Body Color Options



BATTERY

UGR (CIE Pub.117): 20
IEC/EN 62471 Photo-Biologic Protection RG0

LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index




CCT



CONTROL

Rated Input Voltage 220~240VAC
Range of Input Voltage 176~264VAC
Frequency 50~60Hz
Power Factor -
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver

Additional Features



Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts -

Emergency LED Lighting Wall



ED20-W000

Power	Lum. Flux	Efficiency
8W	- lm	- lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



****The specified luminous flux values may vary by %10.**

ORDER CODE EXPANSION

ED20-W000- 008 - X	65	S	-9016-XXXX-	0	S	S	S	20
--------------------	----	---	-------------	---	---	---	---	----

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACCESSORY	IP
ED20	W000	008: 8W		65: 6500K	S: Standart	9016: Beyaz		0: ON-OFF	S: LAMPTIME	S: Standart 1: 1 Hours Kit	S: Standart	20: IP20