



GR22
IP65 Landscape
LED Lighting



HOUSING
Electrostatic powder paint coated extruded aluminum housing
IP65 Protection
IK09 Impact Protection
Electrical Safety Class I

Body Color Options

9006
Gray

7016
Anthracite

9005
Black

OPTIC
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options

30°

60°

90°

35°-85°

Asymmetric

LED
SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index

80⁺
Ra>80

CCT

2700K

3000K

4000K

5000K

5700K

6500K

CONTROL
Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
90~305VAC
50~60Hz
PF>0.95
-40°C ~ +60°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features

0-10V
0-10V Prog.


STANDARDS
Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-3
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

GR22

IP65 Landscape

LED Lighting

 GR22-0301 3m		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>36W</td><td>- lm</td><td>- lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	36W	- lm	- lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
36W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						
 GR22-0401 4m		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>36W</td><td>- lm</td><td>- lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	36W	- lm	- lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
36W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						
 GR22-0601 6m		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>2x36W</td><td>- lm</td><td>- lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	2x36W	- lm	- lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
2x36W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

GR22- 0402 - 036 - 8 40 S - 9005-0120 - V S S S 65												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
GR22	0301 0401 0601	0036: 36W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9006: Gray 7016: Anthracite 9005: Black	0120: 120°	V: 0-10V Prog.	S: LAMPTIME	S: Standart	S: Standart	65: IP65