




IL14

IP65 Waterproof


PC Monobloc LED Lighting



HOUSING

Polycarbonate extruded monoblock housing
IP65 Protection
Electrical Safety Class I

Body Color Options



OPTIC

PC Diffuser
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0


Optic Options




LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index




CCT



CONTROL

Rated Input Voltage	220~240VAC
Range of Input Voltage	176~264VAC
Frequency	50~60Hz
Power Factor	PF>0.95
Operating Temperature	-20°C ~ +50°C
Constant Current LED Driver	Overload Protection (OLP), Overvoltage Protection (OVP), Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



STANDARDS

Luminaire Standarts	EN 60598-1 - EN 60598-2-1
Driver Standarts	LVD (EN 61347-1, EN 61347-2-13) EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

IL14
IP65 Waterproof
PC Monobloc LED Lighting



IL14-0060




Table with 3 columns: Power, Lum. Flux, Efficiency. Values: 15W, 1480 lm, 92 lm/W

Table with 2 columns: Packaging Sizes, Values. Values: Width, Length, Height, Amount per ctn., Ctn. weight, Deci



IL14-0120




Table with 3 columns: Power, Lum. Flux, Efficiency. Values: 30W, 40W, 60W, 3173 lm, 3809 lm, 6026 lm, 110 lm/W, 103 lm/W, 101 lm/W

Table with 2 columns: Packaging Sizes, Values. Values: Width, Length, Height, Amount per ctn., Ctn. weight, Deci



IL14-0150




Table with 3 columns: Power, Lum. Flux, Efficiency. Values: 60W, 5881 lm, 107 lm/W

Table with 2 columns: Packaging Sizes, Values. Values: Width, Length, Height, Amount per ctn., Ctn. weight, Deci

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

IL14 - 0120 - 040 - 8 40 S - 9016-0120- 0 S S S 65

Table with 11 columns: GROUP CODE, BODY CODE, POWER, CRI, CCT, EFFICIENCY, BODY COLOR, OPTIC, CONTROL, DRIVER, KIT, ACCESSORY, IP. Contains detailed specifications for each code.