




LD13

Decorative LED Lighting


Triangle



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP20 Protection
Electrical Safety Class I

Body Color Options



OPTIC

PS diffuser with high transmissivity
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT




CONTROL

Rated Input Voltage 220~240VAC
Range of Input Voltage 176~264VAC
Frequency 50~60Hz
Power Factor PF>0.95
Operating Temperature -20°C ~ +50°C

Constant Current LED Driver

Overload Protection (OLP), Overvoltage Protection (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



STANDARDS

Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

Decorative LED Lighting Triangle

****The specified luminous flux values may vary by %10.**

LD13- 0100 - 075 - 8 40 S -9005-0120- 0 S S S 20

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACCESSORY	IP
LD13	0040	030: 30W	8: 80	27: 2700K	S: Standart	9016: White	0120: 120°	0: ON-OFF	S: LAMPTIME	S: Standart	S: Standart P: Suspended	20: IP20
	0060	045: 45W		30: 3000K		9006: Gray		D: Dali				
	0080	060: 60W		40: 4000K		9005: Black		W: Smart TW				
	0100	075: 75W		65: 6500K								
	0120	090: 90W										