




LD17

Decorative LED Lighting

Square



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP20 Protection
Electrical Safety Class I

Body Color Options



OPTIC

PS diffuser with high transmissivity
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index




CCT



CONTROL

Rated Input Voltage	220~240VAC
Range of Input Voltage	176~264VAC
Frequency	50~60Hz
Power Factor	PF>0.95
Operating Temperature	-20°C ~ +50°C
Constant Current LED Driver	Overload Protection (OLP), Overvoltage Protection (OVP), Short Circuit Protection (SCP), Over Temperature Protection (OTP)

CCT



STANDARDS

Luminaire Standarts	EN 60598-1 - EN 60598-2-1
Driver Standarts	LVD (EN 61347-1, EN 61347-2-13) EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)


LD17

Decorative LED Lighting

Square



LD17-0040



405x405mm

Power	Lum. Flux	Efficiency
30W	- lm	- lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



LD17-0060




605x605mm

Power	Lum. Flux	Efficiency
45W	- lm	- lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-



LD17-0080



805x805mm

Power	Lum. Flux	Efficiency
60W	- lm	- lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Height	- cm
Amount per ctn.	- pcs.
Ctn. weight	- kg
Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

LD17- 0080 - 060 - 8													40	S	- 9005-0120 - O	S	S	S	20
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP							
LD17	0040 0060 0080	030: 30W 045: 45W 060: 60W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 9006: Gray 9005: Black	0120: 120°	O: ON-OFF D: Dali W: Smart TW	S: LAMPTIME	S: Standart	S: Standart P: Suspended	20: IP20							