




LR14

Linear LED Lighting


Recessed 33x35



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP20 Protection
Electrical Safety Class I

Body Color Options



OPTIC

PC diffuser with high transmissivity
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options




LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT




CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264VAC
50~60Hz
PF>0.95
-20°C ~ +50°C

Additional Features



Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

STANDARDS







Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-2
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

LR14

Linear LED Lighting

Recessed 33x35

 LR14-0060		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>18W</td><td>985 lm</td><td>53 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	18W	985 lm	53 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
18W	985 lm	53 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigth	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weighth	- kg																						
Deci	-																						
 LR14-0120		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>36W</td><td>1682 lm</td><td>48 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	36W	1682 lm	48 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
36W	1682 lm	48 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigth	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weighth	- kg																						
Deci	-																						
 LR14-0150		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>45W</td><td>2244 lm</td><td>52 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	45W	2244 lm	52 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
45W	2244 lm	52 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigth	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weighth	- kg																						
Deci	-																						
 LR14-D100		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>30W/m</td><td>1561 lm</td><td>55 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	30W/m	1561 lm	55 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
30W/m	1561 lm	55 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigth	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weighth	- kg																						
Deci	-																						
 Linear Special Measure		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>30W/m</td><td>-</td><td>-</td></tr></table>	Power	Lum. Flux	Efficiency	30W/m	-	-	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
30W/m	-	-																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigth	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weighth	- kg																						
Deci	-																						
 With Weld Special Measure		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>30W/m</td><td>-</td><td>-</td></tr></table>	Power	Lum. Flux	Efficiency	30W/m	-	-	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weighth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weighth	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
30W/m	-	-																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigth	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weighth	- kg																						
Deci	-																						

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

LR14- 0120 - 036 - 8 40 S - 9005-0120- 0 S S S 20											
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY
LR14	0060	018: 18W	8: 80	27: 2700K	S: Standart	9016: White	0120: 120°	0: ON-OFF	S: LAMPTIME	S: Standart	S: Standart
	0120	036: 36W		30: 3000K		9006: Gray		D: DALI		3: 3 Hours Kit	
	0150	045: 45W		40: 4000K		9005: Black		W: Smart TW			
	D100			65: 6500K							