




LS11

Linear LED


Surface Mounted 34x80



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP20 Protection
Electrical Safety Class I


Body Color Options




OPTIC

UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



Reflector Colors



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT




CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264VAC
50~60Hz
PF>0.95
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



STANDARDS

Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

Surface Mounted 34x80

**The specified luminous flux values may vary by %10.

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACCESSORY	IP
LS11	1L08	027: 27W	8: 80	27: 2700K	S: Standard	9016: White	WHXX: White	O: ON-OFF	S: LAMPTIME	S: Standard 3: 3 Hours Kit	S: Standard P: Suspended	20: IP20
	1L12	036: 36W		30: 3000K		9006: Gray	BLXX: Black	D: Dali				
	2L08			40: 4000K		9005: Black	SRXX: Rose Gold	W: Smart TW				
	2L12			65: 6500K		CRXX: Chrome						
						SGXX: Gold						
							MGXX: Gold Mat					
							SMXX: Smoked					
							XX30: 30"					
							XX45: 45"					

LS11

Linear LED Lighting With Diffuser

Surface Mounted 34x80




LS11-1D09



Power	Lum. Flux	Efficiency
27W	1801 lm	66 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Heigth	- cm
Amount per ctn.	- pcs.
Ctn. weighth	- kg
Deci	-



LS11-1D12



Power	Lum. Flux	Efficiency
36W	2165 lm	60 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Heigth	- cm
Amount per ctn.	- pcs.
Ctn. weighth	- kg
Deci	-



LS11-2D09



Power	Lum. Flux	Efficiency
27W	1801 lm	66 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Heigth	- cm
Amount per ctn.	- pcs.
Ctn. weighth	- kg
Deci	-



LS11-2D12



Power	Lum. Flux	Efficiency
36W	2165 lm	60 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Heigth	- cm
Amount per ctn.	- pcs.
Ctn. weighth	- kg
Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

LS11 - 1D12 - 036 - 8 65 S - 9006-0045- 0 S S S 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
LS11	1D09 1D12 2D09 2D12	027: 27W 036: 36W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 9006: Gray 9005: Black	WHXX: White BLXX: Black SRXX: Rose Gold CRXX: Chrome SGXX: Gold MGXX: Gold Mat SMXX: Smoked XX30: 30° XX45: 45°	O: ON-OFF D: Dali W: Smart TW	S: LAMPTIME	S: Standart 3: 3 Hours Kit	S: Standart P: Suspended	20: IP20