



ML61-ML62-ML63-MA60

Magnet LED Lighting

Ø1000mm



TRACK



CE



VOLTAGE



PROTECT.



CLASS III



Ta



MADE IN
TÜRKIYE

HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP20 Protection
Electrical Safety Class III

Body Color Options



9005
Black

OPTIC

PS Diffuser
Lens
UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering index (CRI>80)

Color Rendering Index

80⁺

Ra>80

CCT



2700K



3000K



4000K



5000K



5700K



6500K

CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

48VDC

-

-

-

-20°C ~ +50°C

Overload Protection (OLP), Overvoltage Protection (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



ON/OFF

STANDARDS

Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1


-

ML61-ML62-ML63-MA60


Magnet LED Lighting

Ø1000mm


► ML61 With Diffuser

 ML61-SD18	 177mm	Power	Lum. Flux	Efficiency	Packaging Sizes	
		6W	288 lm	38 lm/W	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-


► ML62 With Lens

 ML62-SL18	 177mm	Power	Lum. Flux	Efficiency	Packaging Sizes	
		6W	621 lm	72 lm/W	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-

► ML63 Spot

 ML63-SR50	 Ø50mm 105mm	Power	Lum. Flux	Efficiency	Packaging Sizes	
		10W	945 lm	83 lm/W	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-

► MA60 Ø1000mm Track

 MA60-R100	 Ø1000mm	Power	Lum. Flux	Efficiency	Packaging Sizes	
		-	-	-	Width	- cm
					Length	- cm
					Height	- cm
					Amount per ctn.	- pcs.
					Ctn. weight	- kg
					Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

ML62- SL18 - 006 - 8 65 S -9005-XXXX- O S S S 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
ML61	SD18	006: 6W	8: 80	27: 2700K	S: Standart	9005: Black		0: ON-OFF	S: LAMPTIME	S: Standart	S: Standart	20: IP20
ML62	SL18	010: 10W		30: 3000K								
ML63	SR50			40: 4000K								
MA60	R100			65: 6500K								