




ML11

Magnet LED Lighting

With Adjustable Diffuser



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP20 Protection
Electrical Safety Class III

Body Color Options



OPTIC

PS Diffuser
UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering index (CRI>80)

Color Rendering Index




CCT



CONTROL

Rated Input Voltage 48VDC
Range of Input Voltage -
Frequency -
Power Factor -
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver

Additional Features



STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts -


ML11

Magnet LED Lighting

With Adjustable Diffuser



ML11-AD30



Power	Lum. Flux	Efficiency
12W	- lm	- lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Heigth	- cm
Amount per ctn.	- pcs.
Ctn. weighth	- kg
Deci	-



ML11-AD60



Power	Lum. Flux	Efficiency
24W	1858 lm	72 lm/W

Packaging Sizes	
Width	- cm
Length	- cm
Heigth	- cm
Amount per ctn.	- pcs.
Ctn. weighth	- kg
Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

ML11- AD30- 012 - 8 40 S - 9005-0120 - O S S S 20													
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP	
ML11	AD30 AD60	012: 12W 024: 24W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9005: Black	0120: 120°	O: ON-OFF D: DALI W: Smart TW	S: LAMPTIME	S: Standart	S: Standart	20: IP20	