




ML30

Magnet LED Lighting Spot



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP20 Protection
Electrical Safety Class III

Body Color Options



OPTIC

Aluminium Reflector
UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

COB LED with a minimum lifetime of 100.000 hours
High color rendering index (CRI>80)

Color Rendering Index



Ra>80


CCT



CONTROL

Rated Input Voltage 48VDC
Range of Input Voltage -
Frequency -
Power Factor -
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver

Additional Features



Overload Protection (OLP), Overvoltage Protection (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)




STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts -

ML30

Magnet LED Lighting

Spot

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>8W</td><td>896 lm</td><td>90 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	8W	896 lm	90 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weigth	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
8W	896 lm	90 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigth	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigth	- kg																						
Deci	-																						
		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>18W</td><td>1576 lm</td><td>84 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	18W	1576 lm	84 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weigth	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
18W	1576 lm	84 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigth	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigth	- kg																						
Deci	-																						
		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>30W</td><td>- lm</td><td>- lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	30W	- lm	- lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigth</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigth</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigth	- cm	Amount per ctn.	- pcs.	Ctn. weigth	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
30W	- lm	- lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigth	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigth	- kg																						
Deci	-																						

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

ML30-	SR55-	018	-	8	65	S	-	9005-	0038-	0	S	S	S	20
GROUP CODE	BODY CODE	POWER		CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL		DRIVER	KIT	ACSESSORY	IP
ML30	SR35 SR55 SR75	008: 8W 018: 18W 030: 30W		8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9005: Black	0038: 38°	O: ON-OFF D: DALI W: Smart TW		S: LAMPTIME	S: Standart	S: Standart	20: IP20