



ML32

Magnet Armatür Spot



TRACK



CE



VOLTAGE



PROTECT.



CLASS III



Ta



MADE IN
TÜRKIYE

HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP20 Protection
Electrical Safety Class III

Body Color Options



9005
Black

OPTIC

UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



38°

LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering index (CRI>80)

Color Rendering Index

80⁺

Ra>80

CCT



2700K



3000K



4000K



5000K



5700K



6500K

CONTROL

Rated Input Voltage 48VDC
Range of Input Voltage -
Frequency -
Power Factor -
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver

Additional Features



ON/OFF

Overload Protection (OLP), Overvoltage Protection (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts -

ML32

Magnet Armatür

Spot



Power	Lum. Flux	Efficiency	Packaging Sizes	
8W	490 lm	67 lm/W	Width	- cm
			Length	- cm
			Heigth	- cm
			Amount per ctn.	- pcs.
			Ctn. weigth	- kg
			Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

ML32-	SS11	-	008	-	8	65	S	-	9005-0038-	O	S	S	S	20
GROUP CODE	BODY CODE	POWER	CRI		CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL		DRIVER	KIT	ACESSORY	IP
ML32	SS11	008: 8W	8: 80		27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9005: Black	0038: 38°	0: ON-OFF		S: LAMPTIME	S: Standart	S: Standart	20: IP20