



ML34

Magnet LED Lighting

With Diffuser



TRACK



CE



VOLTAGE



PROTECT.



CLASS III



Ta



MADE IN
TÜRKİYE

HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP20 Protection
Electrical Safety Class III

Body Color Options



9005
Black

OPTIC

PS Diffuser
UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



120°

LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering index (CRI>80)

Color Rendering Index



Ra>80

CCT



2700K



3000K



4000K



5000K



5700K



6500K

CONTROL

Rated Input Voltage 48VDC
Range of Input Voltage -
Frequency -
Power Factor -

Operating Temperature -20°C ~ +50°C

Constant Current LED Driver Overload Protection (OLP), Overvoltage Protection (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features



ON/OFF




STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts -

ML34

Magnet LED Lighting

With Diffuser

		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>10W</td><td>923 lm</td><td>78 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	10W	923 lm	78 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
10W	923 lm	78 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						
		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>15W</td><td>1489 lm</td><td>83 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	15W	1489 lm	83 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
15W	1489 lm	83 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						
		<table><tr><th>Power</th><th>Lum. Flux</th><th>Efficiency</th></tr><tr><td>20W</td><td>1858 lm</td><td>87 lm/W</td></tr></table>	Power	Lum. Flux	Efficiency	20W	1858 lm	87 lm/W	<table><tr><th colspan="2">Packaging Sizes</th></tr><tr><td>Width</td><td>- cm</td></tr><tr><td>Length</td><td>- cm</td></tr><tr><td>Heigh</td><td>- cm</td></tr><tr><td>Amount per ctn.</td><td>- pcs.</td></tr><tr><td>Ctn. weigh</td><td>- kg</td></tr><tr><td>Deci</td><td>-</td></tr></table>	Packaging Sizes		Width	- cm	Length	- cm	Heigh	- cm	Amount per ctn.	- pcs.	Ctn. weigh	- kg	Deci	-
Power	Lum. Flux	Efficiency																					
20W	1858 lm	87 lm/W																					
Packaging Sizes																							
Width	- cm																						
Length	- cm																						
Heigh	- cm																						
Amount per ctn.	- pcs.																						
Ctn. weigh	- kg																						
Deci	-																						

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

ML34- SR12 - 015 - 8 40 S - 9005-0120 - 0 S S S 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
ML34	SR09 SR12 SR14	010: 10W 020: 15W 020: 20W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9005: Black	0120: 120°	0: ON-OFF	S: LAMPTIME	S: Standart	S: Standart	20: IP20