



OF13

IP67

LED Floodlight



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP67 Protection
Electrical Safety Class I


Body Color Options



OPTIC

UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0


Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT




CONTROL

Rated Input Voltage 220~240VAC
Range of Input Voltage 176~264VAC
Frequency 50~60Hz
Power Factor PF>0.95
Operating Temperature -20°C ~ +50°C

Constant Current LED Driver

Additional Features



Over Current Protection (OCP), Over Voltage Protection (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

STANDARDS

Luminaire Standards
Driver Standards

EN 60598-1 - EN 60598-2-5
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)



Power	Lum. Flux	Efficiency	Packaging Sizes	
20W	2040 lm	115 lm/W	Width	- cm
			Length	- cm
			Height	- cm
			Amount per ctn.	- pcs.
			Ctn. weight	- kg
			Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

OF13- 0166 - 020 - 8		40	S	- 9016-0120 - 0		S	S	S	67			
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
OF13	0166	020: 20W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K MB: Amber RD: Red GR: Green BL: Blue	S: Standart	7037: Dark Gray 7016: Anthracite 9005: Black	0030: 30° 0060: 60° 0090: 90° 0120: 120° AS00: Asymmetric	O: ON-OFF	S: LAMPTIME E: Other	S: Standart	S: Standart	67: IP67