



OW10

IP67 Wallwasher

LED Lighting



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP67 Protection
Electrical Safety Class I

Body Color Options




9006
Gray

OPTIC

PMMA Lens
UGR (CIE Pub.117):9
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>70)

Color Rendering Index

70⁺

Ra>70

CCT



CONTROL

Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264VAC
50~60Hz
PF>0.95

-20°C ~ +50°C

Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features








ON/OFF

STANDARDS

Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-1
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

OW10
IP67 Wallwasher
LED Lighting

 OW10-0017		Power	Lum. Flux	Efficiency	Packaging Sizes	
		6W	640 lm	102 lm/W	Width	- cm
 OW10-0032		Power	Lum. Flux	Efficiency	Packaging Sizes	
		12W	1358 lm	114 lm/W	Width	- cm
 OW10-0047		Power	Lum. Flux	Efficiency	Packaging Sizes	
		18W	2048 lm	120 lm/W	Width	- cm
 OW10-0062		Power	Lum. Flux	Efficiency	Packaging Sizes	
		24W	3390 lm	134 lm/W	Width	- cm
 OW10-0092		Power	Lum. Flux	Efficiency	Packaging Sizes	
		36W	4905 lm	130 lm/W	Width	- cm
 OW10-0122		Power	Lum. Flux	Efficiency	Packaging Sizes	
		48W	3617 lm	70 lm/W	Width	- cm

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

OW10- 0122 - 048 - 8 65 S -9006- 0060- O S S S 67												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
OW10	0017	006: 6W	8: 80	27: 2700K	S: Standart	9006: Gray	0015: 15°	O: ON-OFF	S: LAMPTIME	S: Standart	S: Standart	67: IP67
	0032	012: 12W		30: 3000K			0030: 30°					
	0047	018: 18W		40: 4000K			0V24: 15°-35°					
	0062	024: 24W		65: 6500K			0045: 45°					
	0092	036: 36W		MB: Amber			0060: 60°					
	0122	048: 48W		RD: Red								
				GR: Green								
				BL: Blue								