




PE11
Slim Panel LED Lighting
Clip-In



HOUSING
Electrostatic powder paint coated extruded aluminum housing
IP20 Protection
Electrical Safety Class II

Body Color Options

9016 White

9006 Gray

9005 Black

All Colors

OPTIC
PS diffuser with high transmissivity
UGR (CIE Pub.117):21
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options

PS 76%

POLYSTYRENE

LED
SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index

80⁺

Ra>80

CCT

2700K

3000K

4000K

5000K

5700K

6500K

CONTROL
Rated Input Voltage
Range of Input Voltage
Frequency
Power Factor
Operating Temperature
Constant Current LED Driver

220~240VAC
176~264 VAC
50~60Hz
PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
-20°C ~ +50°C
Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

Additional Features

ON/OFF

DIM

Emergency Lighting




STANDARDS
Luminaire Standarts
Driver Standarts

EN 60598-1 - EN 60598-2-2
LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

PE11

Slim Panel LED Lighting

Clip-In

 PE11-6060		Power	Lum. Flux	Efficiency	Packaging Sizes	
		40W	3243 lm	89 lm/W	Width	- cm
 PE11-3030		Power	Lum. Flux	Efficiency	Packaging Sizes	
		12W	911 lm	74 lm/W	Width	- cm
 PE11-3060		Power	Lum. Flux	Efficiency	Packaging Sizes	
		20W	1747 lm	84 lm/W	Width	- cm
 PE11-3012		Power	Lum. Flux	Efficiency	Packaging Sizes	
		40W	2972 lm	77 lm/W	Width	- cm

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

PE11- 6060- 040 - 8 40 S - 9016- PS76- O S S X 20												
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP
PE11	6060	012: 12W	8: 80	27: 2700K	S: Standart	9016: White	PS76	O: ON-OFF	S: LAMPTIME	S: Standart 3: 3 Hours Kit		20: IP20
	3030	020: 20W		30: 3000K		9006: Gray		D: DALI				
	3060	040: 40W		40: 4000K		9005: Black						
	3012			65: 6500K								